

Sponsor: Vladislav Formánek Mertlin s.r.o. Nerudova 744 Cerveny Kostelec, Náchodský 549 41 Czech Republic

## Bacterial Filtration Efficiency (BFE) Final Report

Test Article: NANO FIBER MASK B, REF 1230500529, lot 20117175

Purchase Order: NR20000432 Study Number: 1376718-S01 Study Received Date: 30 Dec 2020

Testing Facility: Nelson Laboratories, LLC

6280 S. Redwood Rd.

Salt Lake City, UT 84123 U.S.A.

Test Procedure(s): Standard Test Protocol (STP) Number: STP0004 Rev 18

Deviation(s): None

**Summary:** The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial control counts upstream of the test article to the bacterial counts downstream. A suspension of *Staphylococcus aureus* was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at  $1.7 - 3.0 \times 10^3$  colony forming units (CFU) with a mean particle size (MPS) of  $3.0 \pm 0.3 \ \mu m$ . The aerosols were drawn through a six-stage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019, Annex B.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side: Inside BFE Test Area: ~40 cm<sup>2</sup>

BFE Flow Rate: 28.3 Liters per minute (L/min)

Conditioning Parameters: 85 ± 5% relative humidity (RH) and 21 ± 5°C for a minimum of 4 hours

Test Article Dimensions: ~178 mm x ~172 mm

Positive Control Average: 2.1 x 10<sup>3</sup> CFU Negative Monitor Count: <1 CFU

MPS: 2.9 µm





Sean Shepherd electronically approved for

Mikell Goldsberry

21 Jan 2021 20:09 (+00:00)

Study Director

Study Completion Date and Time

801-290-7500

nelsonlabs.com

sales@nelsonlabs.com

FRT0004-0001 Rev 22 Page 1 of 2



## Results:

Test Article Number	Percent BFE (%)
1	99.7
2	99.5
3	>99.9
4	99.8
5	99.9

The filtration efficiency percentages were calculated using the following equation:

$$\% BFE = \frac{C-T}{C} \times 100$$

C = Positive control average

T = Plate count total recovered downstream of the test article Note: The plate count total is available upon request